

YFSPT-3W

Professional Emergency Lighting Fixture



TECHNICAL SPECIFICATIONS

Product Code	YFSPT-3W
Input Voltage	220-240 V AC
Maximum Power	3 W
Battery	3.7 - 3.6 V
Emergency Duration	1-3 Hours
Operating Frequency	50 - 60 Hz
Operating Temperature	-10 °C to +40 °C
Lamp Type	LED
Working Mode	In case of emergency
Light Angle	60 x 120

- 3 W professional emergency lighting fixture
- Heat resistant power LED
- Green LED battery charge indicator
- Red power failure indicator LED
- Battery overcharge and discharge protection
- Activation by interruption of unswitched phase
- High temperature resistant industrial grade
- 3.7 V Li-ion / 3.6 V Ni-Cd battery 6500 K light color
- Test button function
- Wide angle luminous flux
- Recessed and Surface mounting type
- Tolerance to operating temperatures between -10 °C and +40 °C

APPLICATION AREAS



OFFICE



HOTEL



HOSPITAL



INDUSTRIAL

Ideal for all LED lighting systems used in offices, hotels, hospitals, and industrial facilities, ensuring safe evacuation during power outages.

BATTERY

PRODUCT CODE	BATTERY	BATTERY CELL CODE
YFSPT-3W 13L 2H	3.7 V / 1500 mAh	YFP13L Li-ion
YFSPT-3W 23L 3H	3.7 V / 2000 mAh	YFP23L Li-ion
YFSPT-3W 01 1H	3.6 V / 800 mAh	YFP01 Ni-Cd
YFSPT-3W 13 2H	3.6 V / 1500 mAh	YFP13 Ni-Cd
YFSPT-3W 23 3H	3.6 V / 2200 mAh	YFP23 Ni-Cd

DIMENSIONS

